

# DRIED SAND

## PRODUCT DESCRIPTION

Dried Sand can be used in numerous applications including gap filling between paving, in mortar/render mixes and in concrete mixes.

## SUPPLY

Dried Sand is available from most retail hardware and building supply outlets.

Dried Sand is pre-packed into easy to handle 20kg multi-walled paper bags.

## SPECIFICATION

Dried Sand satisfies the requirements of AS2758.1 Table 3 for uncrushed fine aggregate.

All products are manufactured under a third party certified manufacturing and supply quality assurance system to ISO 9001 (BSI Certification No FS 604665).

## APPLICATIONS

Dried Sand has many uses around the home or projects which require a fine sand.

- Gap filling of concrete and clay pavers where a cement mortar or \*Pave Set is not required.  
\*Pave Set is an engineered alternative to Dried Sand; see our product data sheet on this product.
- May be used as a general absorbent for liquids such as motor oil.
- Mixing with paint to provide a non-slip surface.
- As an ingredient in plant potting mixes.
- Mixed 1:10 with cement it will produce a low strength mortar/grout.
- Can be used to make concrete when mixed with cement and a suitable coarse aggregate.

## DIRECTIONS FOR USE WITH PAVING

1. Spread Dried Sand evenly over dry pavers and sweep into the joints with a stiff broom.

2. Spread an extra layer of Dried Sand over the pavers.
3. Vibrate the entire area using a vibrating plate compactor.
4. All excess Dried Sand must be swept up and removed from the paved area.

## HANDLING AND STORAGE

Manual handling of bag products without due care and attention may result in personal injury. Unless you have been trained in manual handling methods it is suggested that you share the load with another person.

Dried Sand can be stored indefinitely in a dry place.

## SAFETY INFORMATION

For safety information refer to the Safety Data Sheet for Dried Sand.

## CONTACT POINTS

**For further information contact the Sales and Marketing Department at:**

Adelaide Brighton Cement Ltd  
ABN 96 007 870 199  
62 Elder Road  
BIRKENHEAD SA 5015

**Telephone: 08 8300 0300**

**Facsimile: 08 8341 1591**

**Web Site: [www.adelaidebrighton.com.au](http://www.adelaidebrighton.com.au)**

### DISCLAIMER

While the information in this Product Data Sheet has been prepared in good faith, Adelaide Brighton Cement Limited does not warrant that the information is accurate, complete or up to date. Each user of any information, or any product referred to, in this Product Data Sheet must:

- determine whether the information or product is suitable for their purpose;
- assess and control any risks associated with the information or product; and
- obtain professional advice in relation to the use of the information or product.

Failure to do so may result in serious damage or injury.

To the extent permitted by law, Adelaide Brighton Cement Limited:

- excludes all representations, warranties and guarantees in relation to any information in this Product Data Sheet; and
- will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Product Data Sheet.

DryPak® and the DryPak® logo, the Adelaide Brighton logo and Adelaide Brighton Cement are registered trade marks of Adelaide Brighton Limited and its related entities.