

**PRODUCT DESCRIPTION**

Adelaide Brighton Cement provides Dried Sand, a natural fine aggregate that can be used in numerous applications including paver joints, mortar, render, and concrete.

SUPPLY

Dried Sand is available from most retail hardware and building supply outlets. It is pre-packed into easy to handle 20 kg multi-walled paper bags.

SPECIFICATION

Dried Sand satisfies the requirements of AS 2758.1.

All products are manufactured under a third-party certified manufacturing and supply quality assurance system to ISO 9001 (BSI Certification No FS 604665).

APPLICATIONS

Dried Sand has many uses in domestic and commercial applications requiring a fine sand.

- Joint filling of concrete and clay pavers where a cement mortar or Pave Set* is not required. *Pave Set is an engineered alternative to Dried Sand. For more information, please refer to our Pave Set product datasheet.
- General absorbent for liquids such as motor oil.
- Combined with paint to provide a non-slip surface.
- Improve drainage in plant potting soils.
- Mixed with cement to produce mortar, grout, or render.
- Mixed with cement and coarse aggregate to produce concrete.

DIRECTIONS FOR USE WITH PAVING

1. Spread Dried Sand evenly over dry pavers and sweep into the joints with a stiff broom.
2. Spread an extra layer of Dried Sand over the pavers.
3. Vibrate the entire area using a vibrating plate compactor.
4. All excess Dried Sand must be swept up and removed from the paved area.

HANDLING AND STORAGE

Manual handling of bag products without due care and attention may result in personal injury. Unless you have been trained in manual handling methods, it is suggested that you share the load with another person.

Dried Sand can be stored indefinitely in a dry place.

SAFETY INFORMATION

For safety information refer to the safety datasheet for Dried Sand.

CONTACT POINTS

For further information contact the Sales and Marketing department at:

Adelaide Brighton Cement Ltd
ABN 96 007 870 199
62 Elder Road
BIRKENHEAD SA 5015

Telephone: 08 8300 0300

Website: www.adelaidebrighton.com.au

DISCLAIMER

While the information in this product datasheet has been prepared in good faith, Adelaide Brighton Cement Limited does not warrant that the information is accurate, complete, or up to date.

Each user of any information, or any product referred to, in this product datasheet must:

- Determine whether the information or product is suitable for their purpose;
- Assess and control any risks associated with the information or product; and
- Obtain professional advice in relation to the use of the information or product.

Failure to do so may result in serious damage or injury.

To the extent permitted by law, Adelaide Brighton Cement Limited:

- Excludes all representations, warranties, and guarantees in relation to any information in this product datasheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special, or economic loss (including, but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this product datasheet.