

Final

**Product Certified:** Hydrated Lime  
**Test Certificate Number:** 240595  
**Customer:** Adbri Cement, Angaston Plant, SA  
**Sample Code:** A08b3eb  
**Sample Date:** 1/10/2024

Reportable Property	Test Method	Requirements of AS1672.1	Result
<b>CHEMICAL ANALYSIS</b>			
Available Lime (CaOH <sub>2</sub> )	AS4489.6.1	Min 65 %	89.8 %
Magnesium Oxide	AS4489.5.1	N/R	0.8 %
Silicon Dioxide	AS4489.5.1	N/R	1.8 %
Carbon Dioxide	BH-TM-0547	Max 4 %	1.9 %
<b>PHYSICAL TESTING</b>			
AS-Sieve - 600µm (Cumul. % Retained)	AS4489.2.1	Max 5 %	< 0.1 %
Soundness - Le Chatelier Test	AS4489.4.1	Max 10 mm	0 mm
Moisture Content	AS4489.8.1	Max 2.5 %	0.8 %

*This document shall not be reproduced except in full.*

**REMARKS**


These test result apply specifically to the sample as received at the Adbri Cement Birkenhead Laboratory (Accreditation number: 252), 62 Elder Rd Birkenhead SA 5015.

This despatch grab sample complies to the requirements of AS1672.1:1997, Hydrated Lime.

N/R = No Requirement



Accredited for compliance with ISO/IEC  
17025 - Testing.



Approved Signatory

M. Wythe

**Issue Date:** 24/11/2024